

COMPACT

V350 WALL MOUNT

YEAST MONITOR RANGE



COMPACT V350 Wall Mount

- Connects to any single COMPACT and is programmable for different applications.
- Provides power to a single COMPACT.
- Provides 2 x 4-20mA current loops for concentration and conductivity.
- Displays graphs of data.
- 1 x Alarm Relay
- IP65 Rated

Description	Part Number
V350 Wall Mount	3520-00
V350 Wall Mount Box with Profibus	3560-00

Technical Specifications


Dimensions	Height: 200 mm (Allow for Cable Entry)	Width: 165 mm
	Depth: (Max) 135 mm	Weight: 2.8 kg
Measuring Ranges	Capacitance: 0 to 400pF/cm, equivalent Cells/ml Conductivity: 1 to 40mS/cm.	
Power Supply:	+24V DC	
Power Consumption:	15W Maximum	
Battery Backup:	7 years typical, at 25°C (Clock and Data Only)	
Electrical Safety:	Must be mounted in a suitable grounding system. Refer to installation instructions.	
Environmental:	IP65 for fascia, when mounted in suitable panel. Safe ambient operating temperature range: 5°C to 40°C Recommended ambient operating temperature range: 15°C to 30°C Relative Humidity: < 85%. Pollution: Deg 2. (EN61010) Recommended operating altitude: < 2000m	

COMPACT

V350 WALL MOUNT

YEAST MONITOR RANGE

Dimensions



V350/V350PB Wall Mount – Front View

Standard version shown, PROFIBUS version has the same dimensions.

